

Memo No. 6638 /NKDA/Engg-36/2010 (VI)

Date: 26.11.2015

**CORRIGENDUM**


**Sub:** Implementation (Supply, Installation, Testing & Commissioning) of an Automated Vacuum Refuse Collection System on Turn-key basis in Eco-Park, New Town, Kolkata along with 05 (five) years comprehensive operation and maintenance.

**Ref :** Notice Inviting e-Tender No. WBNKDA/06/EE-I/NKDA/2015-16/2<sup>nd</sup> Call. circulated vide this office memo no. 6278 /NKDA /Engg-36 /2010 (VI) dated 03.11.2015. of New Town Kolkata Development Authority, 03, MAR, New Town, Kolkata-700156 and subsequent corrigendum issued thereon.

This is to notify that the following Corrigendum is made with reference to the above NIeT and subsequent corrigendum issued thereon.

Sl. No.	Description	As is	Would be
1	<b>Tender Document of NIeT</b> <b>Section – D</b> <b>TECHNICAL SPECIFICATIONS (COLLECTION AND CONVEYANCE )</b> <b>SI No. 3. SOLID WASTE CONVEYANCE PIPE</b> <b>Sl. No. 3.1. Pipe Network</b> <b>SI 3.1.12</b> <b>Page No. 105.</b>	Buried pipes shall be corrosion protected with factory coating comprising 3- Layers PE coating. All pipe joints and pipe to fitting joints shall be fully welded. The maximum internal protrusion of all weld joints shall not exceed 3mm. Pipe supports shall be provided as and when required for stable and sufficient support of the solid waste conveyance pipe. The average distance between supports shall not exceed 3m. All buried pipe supports shall be encased in the water proof concrete and shall be supported, unless otherwise specified. Exposed supports shall be painted only. Suitable vibration isolation pads shall be provided to isolate the pipe from building structure where necessary.	Buried pipes shall be corrosion protected with factory coating comprising 3- Layers PE coating both inside & outside. All pipe joints and pipe to fitting joints shall be fully welded. The maximum internal protrusion of all weld joints shall not exceed 3mm. Pipe supports shall be provided as and when required for stable and sufficient support of the solid waste conveyance pipe. The average distance between supports shall not exceed 3m. All buried pipe supports shall be encased in the water proof concrete and shall be supported, unless otherwise specified. Exposed supports shall be painted only. Suitable vibration isolation pads shall be provided to isolate the pipe from building structure where necessary.


Other terms and conditions of the NIeT & other tender documents shall, however, remain unchanged.

  
**Executive Engineer – I**  
New Town Kolkata Development Authority  
Date: 26.11.2015

Memo No. 6638 /1(8) /NKDA/Engg-36/2010 (VI)

Copy forwarded for information and necessary action to :-

1. The Chief Executive Officer, New Town Kolkata Development Authority.
2. The Chief Engineer, New Town Kolkata Development Authority.
3. The Finance Office, New Town Kolkata Development Authority
4. The Assistant Engineer – I, New Town Kolkata Development Authority.
5. The Estimator/Sr. Accountant / Cashier, New Town Kolkata Development Authority.
6. P.A to the Chairman, New Town Kolkata Development Authority.
7. Office Notice Board.
8. Official Website of New Town Kolkata Development Authority ([www.nkdamar.org](http://www.nkdamar.org))

  
**Executive Engineer – I**  
New Town Kolkata Development Authority